


LC 501 Series

12W/18W/24

CLEAN LIGHT



Technical Specifications

Product Name	: Marker
Housing	: Alu. Die Cast
Heatsink	: Alu. Die Cast
Beam Angle	: 120°
Surface Finish	: White / Black / Grey
Tilt / Rotation	: Fixed
Mounting	: Ceiling mount

LED	: SMD
LED efficacy	: 90 lm / watt
LED CRI	: >80 >90
LED CCT	: 2700K - 6500K
LED Bin	: 5/7 step
LED life	: 50,000 hrs

Input Voltage	: 100-240 V AC
Frequency	: 50~60 Hz
Operating temp	: -20°C ~ +40°C
Driver Surge	: 2.5 / 6.0KV
Power Factor	: 0.95 / 0.5
Ingress Protection	: IP20

System Watt	: 12W/18W/24W
-------------	---------------



Product Parameters

Power:	12W	18W	24W
Item No:	LC5011	LC5012	LC5013
Size(mm):	1000x17x16	1000x170x16	1000x17x16

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 120°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR

-P125-

