



Technical Specifications

Product Name	: Marker
Housing	: Alu. Die Cast
Heatsink	: Alu. Die Cast
Beam Angle	: 12°24°36°45°60°
Surface Finish	: White / Black / Grey
Tilt / Rotation	: Fixed
Mounting	: Recess mount
LED	: COB
LED efficacy	: 100 lm / watt
LED CRI	: >80 >90 >95
LED CCT	: 2700K - 6500K
LED Bin	: 2/3 step
LED life	: 50,000 hrs

Input Voltage	: 100-240 V AC
Frequency	: 50~60 Hz
Operating temp	: -20°C ~ +40°C
Driver Surge	: 2.5 / 6.0KV
Power Factor	: 0.95 / 0.5
Ingress Protection	: IP65 IP44

System Watt	: 12W/18W/24W/30W 35/40W
-------------	-----------------------------



LD701 Series

12W/18W/24W/30W/35W/40W

DOWNLIGHT COB SERIES IP 65



Product Parameters

Power:	12W	18W	24W	30W	35W	40W
Item No:	LD7013	LD7013A	LD7014	LD7014A	LD7015	LD7015A
Cut out:	φ85mm	φ85mm	φ115mm	φ115mm	φ140mm	φ140mm
Size(DxH):	95x89mm	95x89mm	125x113mm	125x113mm	151x132mm	151x132mm

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 12°24°36°45°60°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR



IP 44
IP 65

