


DOWNLIGHT
COB SERIES
IP 65

LD702 Series
12W/18W/24W/30W/35W/40W



Product Parameters

Power:	12W	18W	24W	30W	35W	40W
Item No:	LD7023	LD7023A	LD7024	LD7024A	LD7025	LD7025A
Cut out:	85x85mm		115x115mm		140x140mm	
Size(DxH):	95x95x89mm		125x125x113mm		151x151x132mm	

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 12°24°36°45°60°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR

Technical Specifications

Product Name	: Marker
Housing	: Alu. Die Cast
Heatsink	: Alu. Die Cast
Beam Angle	: 12°24°36°45°60°
Surface Finish	: White / Black / Grey
Tilt / Rotation	: Fixed
Mounting	: Recess mount

LED	: COB
LED efficacy	: 100 lm / watt
LED CRI	: >80 >90 >95
LED CCT	: 2700K - 6500K
LED Bin	: 2/3 step
LED life	: 50,000 hrs

Input Voltage	: 100-240 V AC
Frequency	: 50~60 Hz
Operating temp	: -20° C ~ +40° C
Driver Surge	: 2.5 / 6.0KV
Power Factor	: 0.95 / 0.5
Ingress Protection	: IP65

LED watt	: 8W/12W/18W 25W/30/40W
System Watt	: 9W/13W/19W 26W/32/42W

