

LD702*M Series

1x9W/2x9W/3x9W/4x9W
1x12W/2x12W/3x12W/4x12W

DOWNLIGHT
SMD SERIES
IP 20



Technical Specifications

Product Name	: Marker
Housing	: Alu. Die Cast
Heatsink	: Alu. Die Cast
Beam Angle	: 15°/24°/36°
Surface Finish	: White / Black / Grey
Tilt / Rotation	: Fixed
Mounting	: Surface mount
LED	: SMD
LED efficacy	: 100 lm / watt
LED CRI	: >80 >90 >95
LED CCT	: 2700K - 6500K
LED Bin	: 2/3 step
LED life	: 50,000 hrs

Input Voltage	: 100-240 V AC
Frequency	: 50~60 Hz
Operating temp	: -20°C ~ +40°C
Driver Surge	: 2.5 / 6.0KV
Power Factor	: 0.95 / 0.5
Ingress Protection	: IP65

System Watt	: 1x9W/1x12W
	2x9W/2x12W
	3x9W/3x12W
	4x9W/4x12W



Product Parameters

Power:	1x9/12W	2x9/12W	3x9/12W	4x9/12W
Item No:	LD702-1x12M	LD702-2x12M	LD702-3x12M	LD702-4x12M
Size(LxwxH):	108x108x110mm	202x108x110mm	298x108x110mm	202x202x110mm

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 15°/24°/36°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR



IP 20

