

LD703*M Series

10W/20W/30W/40W/50W

DOWNLIGHT
COB SERIES
IP 65



Technical Specifications

Product Name	: Marker
Housing	: Alu. Die Cast
Heatsink	: Alu. Die Cast
Beam Angle	: 20° / 40°
Surface Finish	: White / Black / Grey
Tilt / Rotation	: Fixed
Mounting	: Surface mount

LED	: COB
LED efficacy	: 90 lm / watt
LED CRI	: >80 >90 >95
LED CCT	: 2700K - 6500K
LED Bin	: 2/3 step
LED life	: 50,000 hrs

Input Voltage	: 100-240 V AC
Frequency	: 50~60 Hz
Operating temp	: -20°C ~ +40°C
Driver Surge	: 2.5 / 6.0KV
Power Factor	: 0.95 / 0.5
Ingress Protection	: IP65 / IP44

System Watt	: 8W/13W/19W/26W
-------------	------------------



Product Parameters

Power:	10W	20W	30W	40W	50W
Item No:	LD7032M	LD7032M	LD7032M	LD7032M	LD7032M
Size(DxH):	75x100mm	95x100mm	115x152mm	140x160mm	170x180mm

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 20°/40°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR