


LD705 Series

7W/12W/18W/24W/30W/40W

DOWNLIGHT COB SERIES IP 65




Technical Specifications

Product Name	: Marker
Housing	: Alu. Die Cast
Heatsink	: Alu. Die Cast
Beam Angle	: 80°
Surface Finish	: White / Black / Grey
Tilt / Rotation	: Fixed
Mounting	: Recess mount
LED	: COB
LED efficacy	: 100 lm / watt
LED CRI	: >80 >90 >95
LED CCT	: 2700K - 6500K
LED Bin	: 2/3 step
LED life	: 50,000 hrs

Input Voltage	: 100-240 V AC
Frequency	: 50~60 Hz
Operating temp	: -20° C ~ +40° C
Driver Surge	: 2.5 / 6.0KV
Power Factor	: 0.95 / 0.5
Ingress Protection	: IP65

System Watt	: 8W/12W/18W
	: 24W/30W/40W



Product Parameters

Power:	7W	12W	18W	24W	30W	40W
Item No:	LD70525	LD7053	LD7054	LD7055	LD7056	LD7058
Cut out:	φ75mm	φ95mm	φ115mm	φ145mm	φ165mm	φ200mm
Size(DxH):	90x44mm	115x48mm	140x52mm	165x55mm	190x60mm	230x64mm

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 80°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR

