


DOWNLIGHT
SMD SERIES
IP 65

LD706 Series
7W/12W/18W/24W/30W/40W



Technical Specifications

Product Name	: Marker
Housing	: Alu. Die Cast
Heatsink	: Alu. Die Cast
Beam Angle	: 100°
Surface Finish	: White / Black / Grey
Tilt / Rotation	: Fixed
Mounting	: Recess mount

LED	: SMD
LED efficacy	: 100 lm / watt
LED CRI	: >80 >90 >95
LED CCT	: 2700K - 6500K
LED Bin	: 2/3 step
LED life	: 50,000 hrs

Input Voltage	: 100-240 V AC
Frequency	: 50~60 Hz
Operating temp	: -20°C ~ +40°C
Driver Surge	: 2.5 / 6.0KV
Power Factor	: 0.95 / 0.5
Ingress Protection	: IP65

System Watt	: 8W/12W/18W 25W/30/40W
-------------	----------------------------



Product Parameters

Power:	9W	12W	18W	24W	30W	40W
Item No:	LD70625	LD7063	LD7064	LD7065	LD7066	LD7068
Cut out:	φ75mm	φ95mm	φ115mm	φ145mm	φ165mm	φ200mm
Size(DxH):	90x44mm	115x48mm	140x52mm	165x55mm	190x60mm	230x64mm

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 100°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR

