


Ld708 Series

8W/12W/15W/20W/30W/40W

DOWNLIGHT
COB SERIES
IP 20



Technical Specifications

Product Name	: Marker
Housing	: Alu. Die Cast
Heatsink	: Alu. Die Cast
Beam Angle	: 24° 40° 60°
Surface Finish	: White / Black / Grey
Tilt / Rotation	: Fixed
Mounting	: Recess mount
LED	: SMD
LED efficacy	: 100 lm / watt
LED CRI	: >80 >90 >95
LED CCT	: 2700K - 6500K
LED Bin	: 2/3 step
LED life	: 50,000 hrs

Input Voltage	: 100-240 V AC
Frequency	: 50~60 Hz
Operating temp	: -20° C ~ +40° C
Driver Surge	: 2.5 / 6.0KV
Power Factor	: 0.95 / 0.5
Ingress Protection	: IP20

System Watt	: 8W/12W/15W
	: 20W/30/40W



Product Parameters

Power:	9W	12W	15W	20W	30W	40W
Item No:	LD70825	LD7083	LD7084	LD7085	LD7086	LD7088
Cut out:	φ75mm	φ90mm	φ110mm	φ135mm	φ160mm	φ190mm
Size(DxH):	93x45mm	110x50mm	135x60mm	165x65mm	192x75mm	225x85mm

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 24° 40° 60°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR



IP 20
IP 41

