

LD709 Series

12W/18W/24W

DOWNLIGHT
COB SERIES
IP 20



Technical Specifications

Product Name	: Marker
Housing	: Alu. Die Cast
Heatsink	: Alu. Die Cast
Beam Angle	: 100°
Surface Finish	: White / Black / Grey
Tilt / Rotation	: Fixed
Mounting	: Recess mount
LED	: SMD
LED efficacy	: 90 lm / watt
LED CRI	: >80 >90
LED CCT	: 2700K - 6500K
LED Bin	: 2/3 step
LED life	: 50,000 hrs

Input Voltage	: 100-240 V AC
Frequency	: 50~60 Hz
Operating temp	: -20° C ~ +40° C
Driver Surge	: 2.5 / 6.0KV
Power Factor	: 0.95 / 0.5
Ingress Protection	: IP20

System Watt	: 12W/18W/24W
	: 26W/31/40W



Product Parameters

Power:	12W	18W	24W
Item No:	LD094	LD7095	LD7096
Cut out:	φ110mm	φ145mm	φ165mm
Size(DxH):	120x50mm	155x55mm	175x55mm

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 100°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR

