

GRILLELIGHT

LG9712 Series
2x8W/2x12W / 2x18W/2x30W



Technical Specifications

Product Name	: Marker
Housing	: Alu. Die Cast
Heatsink	: Alu. Die Cast
Beam Angle	: 15°/24°/36°
Surface Finish	: White / Black / Grey
Tilt / Rotation	: Fixed
Mounting	: Recess mount

LED	: COB
LED efficacy	: 90 lm / watt
LED CRI	: >80 >90 >95
LED CCT	: 2700K - 6500K
LED Bin	: 2/3 step
LED life	: 50,000 hrs

Input Voltage	: 100-240 V AC
Frequcy	: 50~60 Hz
Operating temp	: -20° C ~ +40° C
Driver Surge	: 2.5 / 6.0KV
Power Factor	: 0.95 / 0.5
Ingress Protection	: IP20

System Watt	: 2x8W/2x12W 2x18W/2x(24-30) W
-------------	-----------------------------------



Product Parameters

Power:	2x8W	2x12W	2x18W	2x(24-30)W
Item No:	LS9712	LS9712M	LS9712L	LS9712X
Cut out:	150x75mm	195x95mm	230x120mm	305x160mm
Size(DxH):	160x90x80mm	210x112x85mm	250x137x100mm	325x175x120mm

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 15°/24°/36°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR

