

HIGH BAY LIGHT

LH 910 Series

100W/150W/200W/240W



Technical Specifications

Product Name	: Marker
Housing	: Alu. Die Cast
Heatsink	: Alu. Die Cast
Beam Angle	: 70°
Surface Finish	: White / Black
Tilt / Rotation	: Fixed
Mounting	: Hang mount
LED	: SMD
LED efficacy	: 90 lm / watt
LED CRI	: >70 >80
LED CCT	: 2700K - 6500K
LED Bin	: 5/7 step
LED life	: 50,000 hrs

Input Voltage	: 100-240 V AC
Frequency	: 50~60 Hz
Operating temp	: -20°C ~ +40°C
Driver Surge	: 2.5 / 6.0KV
Power Factor	: 0.95 / 0.5
Ingress Protection	: IP65

System Watt	: 50W/100W 150W/200W
-------------	-------------------------



Product Parameters

Power:	100W	150W	200W	240W
Item No:	LH 9101	LH9102	LH 9103	LH 9104
Size(DxH):	φ260x108mm	φ300x108mm	φ340xL108mm	φ360x108mm

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 70°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR