

HIGH BAY LIGHT

LT 904 Series
18W/24W / 30W/45W



Product Parameters

Power:	100W	150W	200W
Item No:	LH9111	LH9112	LH9113
Size(DxH):	φ240x105mm	φ280x105mm	φ320xL105mm

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector


High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 60°/90°/120°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR



Technical Specifications

Product Name	: Marker
Housing	: Alu. Die Cast
Heatsink	: Alu. Die Cast
Beam Angle	: 60° 90° 120°
Surface Finish	: White / Black / Grey
Tilt / Rotation	: Fixed
Mounting	: Hang mount

LED	: SMD
LED efficacy	: 160 lm / watt
LED CRI	: >70 >80
LED CCT	: 2700K - 6500K
LED Bin	: 5/7 step
LED life	: 50,000 hrs

Input Voltage	: 100-240 V AC
Frequency	: 50~60 Hz
Operating temp	: -20° C ~ +40° C
Driver Surge	: 2.5 / 6.0KV
Power Factor	: 0.95 / 0.5
Ingress Protection	: IP65

System Watt	: 100W/150W 200W/240W
-------------	--------------------------

