

LO A Series

36W/42W/72W




Technical Specifications

Product Name	: Marker
Housing	: Alu. Die Cast
Heatsink	: Alu. Die Cast
Beam Angle	: 120°
Surface Finish	: White / Black / Grey
Tilt / Rotation	: Fixed
Mounting	: Recessed mount
LED	: SMD
LED efficacy	: 80 lm / watt
LED CRI	: >80 >90 >95
LED CCT	: 2700K - 6500K
LED Bin	: 2/3 step
LED life	: 50,000 hrs

Input Voltage	: 100-240 V AC
Frequency	: 50~60 Hz
Operating temp	: -20°C ~ +40°C
Driver Surge	: 2.5 / 6.0KV
Power Factor	: 0.95 / 0.5
Ingress Protection	: IP20

System Watt : 36W/42W/72W



Product Parameters

Power:	36W	42W	72W
Item No:	LOA6060	LOA1203	LOA1206
Size(mm):	600x600x35	1200x300x35	1200x600x35

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 120°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR



IP 20
IP 41

