

TRI-PROOF LIGHT

LP302 Series
20W/30W/40W



Technical Specifications

Product Name	:
Housing	: Polycarbonate
Heatsink	: Polycarbonate
Beam Angle	: 120°
Surface Finish	: White / Black
Tilt / Rotation	: Fixed
Mounting	: Ceiling mount
LED	: SMD
LED efficacy	: 90 lm / watt
LED CRI	: >80 >90
LED CCT	: 2700K - 6500K
LED Bin	: 5/7 step
LED life	: 50,000 hrs

Input Voltage	: 100-240 V AC
Frequcy	: 50~60 Hz
Operating temp	: -20° C ~ +40° C
Driver Surge	: 2.5 / 6.0KV
Power Factor	: 0.95 / 0.5
Ingress Protection	: IP65

System Watt	: 20W/30W/40W
-------------	---------------



Product Parameters

Power:	18W	24W	30W
Item No:	LP3021	LP3022	LP3023
Size(mm):	600x75x70	900x75x70	1200x75x70

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 15°/24°/36°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR

