

LP303 Series

1x20W/2x20W



Technical Specifications

Product Name	:	
Housing	:	Polycarbonate
Heatsink	:	Polycarbonate
Beam Angle	:	120°
Surface Finish	:	White / Black
Tilt / Rotation	:	Fixed
Mounting	:	Ceiling mount
LED	:	LED-T8
LED efficacy	:	90 lm / watt
LED CRI	:	>70 >80
LED CCT	:	2700K - 6500K
LED Bin	:	5/7 step
LED life	:	50,000 hrs

Input Voltage	:	100-240 V AC
Frequency	:	50~60 Hz
Operating temp	:	-20°C ~ +40°C
Driver Surge	:	2.5 / 6.0KV
Power Factor	:	0.95 / 0.5
Ingress Protection	:	IP65

System Watt	:	1x20W/2x20W
-------------	---	-------------

	:	
--	---	--

	:	
--	---	--

	:	
--	---	--

	:	
--	---	--

	:	
--	---	--

	:	
--	---	--

	:	
--	---	--

	:	
--	---	--

Product Parameters

Power:	1x20W	2x20W
Item No:	LP3031	LP3032
Size(mm):	1260x75x96	1260x106x96

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 120°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR