

LP903 Series

1x40W/2x40W



Technical Specifications

Product Name	:	
Housing	:	Polycarbonate
Heatsink	:	Polycarbonate
Beam Angle	:	120°
Surface Finish	:	White / Black
Tilt / Rotation	:	Fixed
Mounting	:	Ceiling mount

LED	:	LED-T8
LED efficacy	:	
LED CRI	:	
LED CCT	:	
LED Bin	:	
LED life	:	50,000 hrs

Input Voltage	:	100-240 V AC
Frequency	:	50~60 Hz
Operating temp	:	-20°C ~ +40°C
Driver Surge	:	2.5 / 6.0KV
Power Factor	:	0.95 / 0.5
Ingress Protection	:	IP65

System Watt	:	1x40W/2x40W
-------------	---	-------------



Product Parameters

Power:	1x40W	2x40W
Item No:	LP9031	LP9032
Size(mm):	1275x105x98	1275x140x98

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 120°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR