

LS902 Series

9W/12W/18W/24W

SPOTLIGHT
COB SERIES



Technical Specifications

Product Name	: Marker
Housing	: Alu. Die Cast
Heatsink	: Alu. Die Cast
Beam Angle	: 15°/24°/36°
Surface Finish	: White / Black / Grey
Tilt / Rotation	: Fixed
Mounting	: Recess mount

LED	: COB
LED efficacy	: 90 lm / watt
LED CRI	: >80 >90 >95
LED CCT	: 2700K - 6500K
LED Bin	: 2/3 step
LED life	: 50,000 hrs

Input Voltage	: 100-240 V AC
Frequency	: 50~60 Hz
Operating temp	: -20°C ~ +40°C
Driver Surge	: 2.5 / 6.0KV
Power Factor	: 0.95 / 0.5
Ingress Protection	: IP20

System Watt	: 9W/12W/18W/24W
-------------	------------------

--	--

--	--

--	--



Product Parameters

Power:	9W	12W	18W	24W
Item No:	LS9022	LS9023	LS9024	LS9024
Cut out:	φ75mm	φ95mm	φ120mm	φ140mm
Size(DxH):	88x95mm	105x95mm	135x100mm	155x110mm

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 15°/24°/36°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR

