

LS911 Series

8W / 12W / 18W

SPOTLIGHT
COB SERIES
IP 65



Technical Specifications

Product Name	: Marker
Housing	: Alu. Die Cast
Heatsink	: Alu. Die Cast
Beam Angle	: 15° 24° 38°
Surface Finish	: White / Black / Grey
Tilt / Rotation	: Fixed
Mounting	: Recess mount
LED	: COB
LED efficacy	: 80 lm / watt
LED CRI	: >80 >90 >95
LED CCT	: 2700K - 6500K
LED Bin	: 2/3 step
LED life	: 50,000 hrs

Input Voltage	: 100-240 V AC
Frequency	: 50~60 Hz
Operating temp	: -20°C ~ +40°C
Driver Surge	: 2.5 / 6.0KV
Power Factor	: 0.95 / 0.5
Ingress Protection	: IP65

System Watt	: 8W/12W/18W
-------------	--------------



Product Parameters

Power:	8W	12W	18W
Item No:	LS9111	LS9112	LS9113
Cut out:	φ55mm	φ75mm	φ95mm
Size(DxH):	65x70mm	90x90mm	108x105mm

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 15° 24° 38°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR



IP 44
IP 65

