


# TRACK LIGHT

## LT 902 Series

20W/25W / 30W/40W



### Product Parameters

|            |            |            |            |            |
|------------|------------|------------|------------|------------|
| Power:     | 20W        | 25W        | 30W        | 40W        |
| Item No:   | LT 9021    | LT 9021A   | LT 9022    | LT 9022A   |
| Size(DxH): | φ75xL104mm | φ75xL104mm | φ98xL112mm | φ98xL112mm |

### Construction

Aluminium Die-Cast heatsink and Frame.  
M. S. CRCA Back body  
Passive cooling design for heat dissipation.

### LED

Bridgelux  
Citizen  
Lumiled  
Cree

### Reflector


High reflection Aluminium / PC reflector  
Color - silver / Golden  
Beam angle - 15° 24° 36° 45° 60°

### Driver

BAG  
Osram  
Philips  
Argo

### Finish

○ ● ●  
WH BL GR



### Technical Specifications

|                 |                        |
|-----------------|------------------------|
| Product Name    | : Marker               |
| Housing         | : Alu. Die Cast        |
| Heatsink        | : Alu. Die Cast        |
| Beam Angle      | : 15° 24° 36° 45° 60°  |
| Surface Finish  | : White / Black / Grey |
| Tilt / Rotation | : Fixed                |
| Mounting        | : Track mount          |
| LED             | : COB                  |
| LED efficacy    | : 90 lm / watt         |
| LED CRI         | : >80 >90 >95          |
| LED CCT         | : 2700K - 6500K        |
| LED Bin         | : 2/3 step             |
| LED life        | : 50,000 hrs           |

|                    |                   |
|--------------------|-------------------|
| Input Voltage      | : 100-240 V AC    |
| Frequency          | : 50~60 Hz        |
| Operating temp     | : -20° C ~ +40° C |
| Driver Surge       | : 2.5 / 6.0KV     |
| Power Factor       | : 0.95 / 0.5      |
| Ingress Protection | : IP20            |

|             |                   |
|-------------|-------------------|
| System Watt | : 20W/25W/30W/40W |
|-------------|-------------------|

