

SPOTLIGHT
SMD SERIES

LW954 Series
8W



Product Parameters

Power:	8W	8W
Item No:	LW9542	LW9542F
Cut out:	70x70mm	70x70mm
Size(DxH):	75x75x42mm	90x75x42mm

Construction

Aluminium Die-Cast heatsink and Frame.
M. S. CRCA Back body
Passive cooling design for heat dissipation.

LED

Bridgelux
Citizen
Lumiled
Cree

Reflector

High reflection Aluminium / PC reflector
Color - silver / Golden
Beam angle - 15°/24°/36°

Driver

BAG
Osram
Philips
Argo

Finish

○ ● ●
WH BL GR



Technical Specifications

Product Name	: Marker
Housing	: Alu. Die Cast
Heatsink	: Alu. Die Cast
Beam Angle	: 15°/24°/36°
Surface Finish	: White / Black / Grey
Tilt / Rotation	: Fixed
Mounting	: Recess mount
LED	: SMD
LED efficacy	: 90 lm / watt
LED CRI	: >80 >90 >95
LED CCT	: 2700K - 6500K
LED Bin	: 2/3 step
LED life	: 50,000 hrs

Input Voltage	: 100-240 V AC
Frequency	: 50~60 Hz
Operating temp	: -20° C ~ +40° C
Driver Surge	: 2.5 / 6.0KV
Power Factor	: 0.5
Ingress Protection	: IP20

System Watt	: 8W/8W
-------------	---------

